



RENZACCI



Multisolvent Versions
HFT HFD HFC

EXCELLENCE
KUJL 30-35

KWL EXCELLENCE

HFT HFD HFC

			EXCELLENCE				EXCELLENCE		
			KWL	30	35		KWL	30	35
Portata per carica	Capacité par cycle	Capacidad	kg	11	15	Load capacity	lb.	26	35
Diametro	Diamètre	Diámetro	mm	725	850	Diameter	in.	28.5	33.6
Profondità	Profondeur	Profundidad	mm	533	533	Depth	in.	21	21
Volume	Volume	Volumen	dm ³	220	300	Volume	cu.ft.	7.8	10.7
Velocità lavaggio	Vitesse de lavage	Velocidad lavado	g/l'	45	42	Wash speed	r.p.m.	45	42
Velocità Centrifuga	Vitesse d'essorage	Velocidad centrifuga	g/l'	500	500	Extract speed	r.p.m.	500	500
Diametro oblò	Diamètre hublot	Diámetro puerta de carga	mm	510	510	Door diameter	in.	20	20
Capacità filtri:	Capacité filtres:	Capacidad filtros:				Filter capacity:			
Filtro nylon/Eco.	Filtre Nylon/Eco.	Filtro Nylon/Eco.	m ²	2.3	4	Nylon filter/Eco.	sq.ft.	22	43
Filtro decolorante	Filtre Décolorant	Filtro descolorante	N°	1	1	Decolorating filter	N°	1	1
Filtro cartuccia	Filtre cartouches	Filtro cartucha	N°	2x 1/2	2x 1.5	Cartridge Filter	N°	2x 1/2	2x 1.5
1° Serbatoio	1° Réservoir	1° depósito	lt	110	150	1st Tank	U.S.gals	29	39.6
2° Serbatoio	2° Réservoir	2° depósito	lt	70	150	2nd Tank	U.S.gals	18,5	39.6
Motori:	Moteurs:	Motores:				Motors:			
Lavaggio/Centrifuga	Lavage/Essorage	Lavado/Centrifuga	kw	1.1	1.5	Wash/Extract	kw	1.1	1.5
Ventilatore	Ventilateur	Ventilador	kw	0.75	1.5	Fan	kw	0.75	1.5
Pompa	Pompe	Bomba	kw	0.55	1.1	Pump	kw	0.55	1.1
Filtro	Filtre	Filtro	kw	0.25	0.33	Filter	kw	0.25	0.33
Gruppo frigo	Groupe Frigo	Grupo frigo	kw	2.6	2.6	Refrigerating unit	kw	2.6	2.6
Misure ingombro:	Dimensions:	Medidas:				Overall dimensions:			
Larghezza	Largeur	Ancho	mm	1010	1200	Width	in.	39.7	47.3
Profondità	Profondeur	Profundidad	mm	1500	2150	Depth	in.	59	85
Altezza	Hauteur	Altura	mm	1960	1230	Height	in.	77,2	83.8
Potenza impiegata:	Puissance employée:	Potencia empleada:				Installed power:			
Versione vapore	Version vapeur	Versión vapor	kw	4.2	6.5	Steam model	kw	4.2	6.5
Versione elettrica	Version électrique	Versión eléctrica	kw	7	12	Electric model	kw	7	12
Peso	Poids	Peso	kg	950	1300	Weight	lb.	2090	2860
Ingresso acqua	Entrée eau	Entrada agua	Ø	½"	½"	Water inlet	Ø	½"	½"
Pressione acqua	Pression eau	Presión agua	bar	1.5	1.5	Water pressure	p.s.i.	21.5	21.5
Ingresso vapore	Entrée vapeur	Entrada vapor	Ø	½"	½"	Steam supply	Ø	½"	½"
Pressione vapore	Pression vapeur	Presión vapor	bar	4.5	4.5	Steam pressure max	p.s.i.	64	64

Descrizioni, dati, misure, colori, non sono impegnativi e possono variare senza alcun preavviso - Description, weights, measurements, pictures and colours are not binding and are subject to change without prior notice - Descriptions, poids, mesures, figures et couleurs sont donnés sans engagement de notre part - Beschreibungen, Gewichte, Maße, Bilder und Farben sind unverbindlich - Descripción, datos, medidas y colores, se facilitan sin compromiso y pueden ser variados sin previo aviso.



EPA



Lloyd's R. of Shipping



ČESKÁ INSP.

OSHA



FACTORY MUTUAL



RENZACCI S.p.A.

Via Morandi, 13 - 06012 CITTÀ DI CASTELLO (PG) - ITALY
 Telefono +39-075-862961 Fax +39-075-8559020
 E-MAIL: renzacci@renzacci.it INTERNET: <http://www.renzacci.it>